



■ QQ : 27450728

■ Web : www.anbermachine.com

■ Email : sales@anber-inc.com



描述

塑料包线机组用于生产PVC聚氯乙烯塑料绝缘电线。更换机头及相应辅机设备，可生产各种不同规格的绝缘电线。本机组挤出机、牵引机采用YCT系列调速电动机，调速范围大；机筒、机头的加热温度采用智能温度控制仪自动控制，灵敏度高。机组结构简单、操作方便、安全可靠。

Detailed description:

Wire PVC coating line is used to produce PVC insulated wire, the customer can produce insulated wire of different size by change the machine head and related accessories. The extruder and tractor apply YCT series governor motor with big range of speed adjustment; we use the intelligent temperature control instrument to control the temperature of the capstan and head automatically with high sensitivity. The structure of the production line is simple, easy to operate, safe and reliable.

技术参数 Technical Parameter

Screw dia.	65mm
Screw length	1625mm
Aspect ratio	25:1
Screw rotate speed	4-40r/min
Motor	Y160M-4;11KW
Capstan heating and cooling	5KW
Machine head heating power	0.7KW
Center height of the machine	1000mm
Machine weight	450Kg

螺杆直径	65mm
螺杆工作长度	1625mm
螺杆长径比	25:1
螺杆转速	4-40r/min
电机	Y160M-4;11KW
机筒加热与冷却	5KW
机头加热功率	0.7KW
机组中心高	1000mm
重量	450Kg



水槽
Channel

Address: NO. 525, Jindong Road Jinxi Industrial Zone, Kunshan, Suzhou city, China.
Web: www.wireweldingmachine.com; www.china-anbermachine.com
Tel: (+86)-510-88239310/88239309 **Fax:** (+86)-510-88236613
Email: sales@anber-inc.com